Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 194554

Microsemi LAWRENCE

TECHNICAL DATA

PNP LOW POWER SILICON TRANSISTOR

Qualified per MIL-PRF-19500/485

Devices		*Qualified Level*
2N5415	**2N5416**	**JAN**
2N5415S	**2N5416S**	**JANTX**
		JANTXV

MAXIMUM RATINGS

Ratings	Symbol	2N5415	2N5416	Units
Collector-Emitter Voltage	V_{CEO}	200	300	Vdc
Collector-Base Voltage	V_{CBO}	200	350	Vdc
Emitter-Base Voltage	V_{EBO}	6.0		Vdc
Collector Current	I_C	1.0		Adc
Total Power Dissipation @ $T_A = +25^0C$ @ $T_C = +25^0C$	P_T	0.75 10		W W
Operating & Storage Temperature Range	T_{op}, T_{stg}	-65 to +200		^0C

THERMAL CHARACTERISTICS

Characteristics	Symbol	Max.	Unit
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	17.5	$^0C/W$

1) Derate linearly 4.28 mW/^{0}C for $T_A > +25^0C$
2) Derate linearly 57.1 mW/^{0}C for $T_C > +25^0C$

TO- 5*
2N5415, 2N5416



2N5415S, 2N5416S
TO-39*
(TO-205AD)

*See appendix A for package outline

ELECTRICAL CHARACTERISTICS ($T_A = 25^0C$ unless otherwise noted)

Characteristics		Symbol	Min.	Max.	Unit
OFF CHARACTERISTICS					
Collector-Emitter Cutoff Current					
V_{CE} = 150 Vdc	2N5415	I_{CEO}		50	µAdc
V_{CE} = 200 Vdc	2N5415			1.0	mAdc
V_{CE} = 250 Vdc	2N5416			50	µAdc
V_{CE} = 300 Vdc	2N5416			1.0	mAdc
Emitter-Base Cutoff Current		I_{EBO}			µAdc
V_{EB} = 6.0 Vdc				20	
Collector-Emitter Cutoff Current					
V_{CE} = 200 Vdc, V_{BE} = 1.5 Vdc	2N5415	I_{CEX}		50	µAdc
V_{CE} = 300 Vdc, V_{BE} = 1.5 Vdc	2N5416			50	µAdc
Collector-Base Cutoff Current					
V_{CB} = 175 Vdc	2N5415	I_{CBO1}		50	µAdc
V_{CB} = 280 Vdc	2N5416			50	
Collector-Base Cutoff Current					
V_{CB} = 200 Vdc	2N5415	I_{CBO2}		500	µAdc
V_{CB} = 350 Vdc	2N5416			500	

ELECTRICAL CHARACTERISTICS (con't)

Characteristics	Symbol	Min.	Max.	Unit
ON CHARACTERISTICS (3)				
Forward-Current Transfer Ratio I_C = 50 mAdc, V_{CE} = 10 Vdc I_C = 1.0 mAdc, V_{CE} = 10 Vdc	h_{FE}	30 15	120	
Collector-Emitter Saturation Voltage I_C = 50 mAdc, I_B = 5.0 mAdc	$V_{CE(sat)}$		2.0	Vdc
Base-Emitter Voltage I_C = 50 mAdc, V_{CE} = 10 Vdc	V_{BE}		1.5	Vdc
DYNAMIC CHARACTERISTICS				
Magnitude of Common Emitter Small-Signal Short Circuit Forward Current Transfer Ratio I_C = 10 mAdc, V_{CE} = 10 Vdc, f = 5.0 MHz	$\lvert h_{fe} \rvert$	3.0	15	
Forward Current Transfer Ratio I_C = 5.0 mAdc, V_{CE} = 10 Vdc, f = 1.0 kHz	h_{fe}	25		
Output Capacitance V_{CB} = 10 Vdc, I_E = 0, 100 kHz ≤ f ≤ 1.0 MHz	C_{obo}		15	pF
Input Capacitance V_{EB} = 5.0 Vdc, I_C = 0, 100 kHz ≤ f ≤ 1.0 MHz	C_{ibo}		75	pF
SWITCHING CHARACTERISTICS				
Turn-On Time V_{CC} =200 Vdc, I_C = 50 mAdc, I_{B1}= 5.0 mAdc	t_{on}		1.0	µs
Turn-Off Time V_{CC} = 200 Vdc, I_C = 50 mAdc, I_{B1} = I_{B2} = 5.0 mAdc	t_{off}		10	µs

SAFE OPERATING AREA

DC Tests

T_C = +25^{0}C; 1 Cycle; t = 0.4 s

Test 1

V_{CE} = 10 Vdc, I_C = 1.0 Adc

Test 2

V_{CE} = 100 Vdc, I_C = 100 mAdc

Test 3

V_{CE} = 200 Vdc, I_C = 24 mAdc 2N5415

Test 4

V_{CE} = 300 Vdc, I_C = 10 mAdc 2N5416

(3) Pulse Test: Pulse Width = 300µs, Duty Cycle ≤ 2.0%.